



DESIGN SPECIFICATIONS

High quality, reliable and complete power unit.
 Compact design
 Easy start and maintenance.
 Every generating set is subject to a comprehensive test Programme which includes full load testing and checking and providing all control and safety shut down functions testing.
 Fully engineered with a wide range of options and accessories, Canopy, soundproof canopy and on road trailer.



400 / 230 V - 50Hz		AJD 165		AJD 170		AJD 200	
Power Factor 0.8	Standby	kVA	165	170	200		
	Prime	kVA	150	155	180		

Standby: Continuous running at variable load for duration of an emergency. No overload is permitted on these ratings. In accordance with BS 5514, ISO 3046.
Prime: Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period. In accordance with ISO 8528, ISO 3046.

ENGINE

JOHN DEERE heavy duty diesel engine.
 Four cycle, water cooled turbo charged.
 Mechanical governor control system, direct injection fuel system.
 Changeable wet type cylinder liners.
 12 V.D.C.starter and charge alternator.
 Replaceable cartridge type air filter,fuel filter and oil filter.
 Cooling radiator and fan.
 Flexible fuel connection hoses and sump oil drain valve.
 Industrial capacity exhaust silencer and steel bellow.
 Starter battery (with lead acid) including rack and cables.
 Jacket water heater (at automatic models).
 Manual and circuit diagram documents.

ALTERNATOR

Newage Stamford brushless single bearing system, 4 Pole.
 Insulation class H.
 Standard degree of protection IP21 .
 Self-exciting and self-regulating.
 Solid state automatic voltage regulator.
 Stator windings with 2/3 pitch for improved harmonics.
 Vacuum Impregnation windings with tropicalized epoxy varnished.

CHASSIS

Steel chassis and antivibration pads.
 Base frame design incorporates an integral fuel tank.
 The generating set can be lifted or pushed / pulled by the base.
 Dial type fuel gauge and drain plug.
 Forklift pockets within base frame.

CANOPY

All canopy parts are designed with modular principles.
 Without welding assembly.
 To enable for lifting, easy maintenance and operation.
 canopies are painted by electrostatic polyester powder paint.
 Exhaust silencer is protected against environmental influences .
 Emergency stop push button is installed outside of canopy .
 Modular canopy can also be installed at a later date.
 Easy maintenance and operation.
 Easy lifting and moving.
 Thermally insulated engine exhaust system.

QUALITY STANDARDS

The equipment meets the following standards: ISO 3046, VDE 0530, BS 4999, BS 5000, IEC 34-1. The generating set is manufactured by a full accredited ISO 9001 NQA

CONTROL SYSTEMS

Deep Sea Control, Supervision and Protection Panel Mounted on genset base frame. The control panel is equipped as follows;
Auto Mains Failure Control Panel P300
 Control panel requirements.
 Control with DSE 720 Features.
 Static Battery Charger.
 Emergency stop-push button.

Generating Set Control Module DSE 720 Features
 Module is used to monitor a mains supply and automatically start a standby generator set.
 Scrolling Digital LCD Panel.
 Front panel configuration of timers and alarm trip points.
 Easy push button control.
 OFF - MANUAL-AUTO-TEST-START
 LCD display scroll push button.

Metering via LCD Display

Generator Volt (F-N).	- Engine oil pressure.
Generator Ampere (L1, L2, I	- Engine speed,
Generator Frequency (Hz).	- Engine hours run.
Mains Volts (F-F/F-N).	- Plant battery volt.
Engine temperature.	

Alarms

Over current.	- High engine temperature.
Over Speed.	- Low battery volt.
Under / Over mains volt.	- Charge fail.
Under / Over mains frequency.	- Start failure.
Low oil pressure.	- Emergency stop.

LED Indications

Mains available.	- Generator available.
Mains on load.	- Generator on load.

Power Outlet-Terminal Board Mounted on the Genset Base Frame.



DSE 720

TECHNICAL DATA**DIESEL GENERATING SETS 400 / 230 V - 50Hz**

MODEL		AJD165			AJD170			AJD200			
Power Pf. 0.8	Standby	kVA	165			170			200		
		Kw	132			136			160		
	Prime	Kva	150			155			180		
		Kw	120			124			144		
Engine Make		John deere			John Deere			John deere			
Model		6068 H			6068 H			6068 H			
Gross Engine Power Output		kWm	153			153			183		
(at rated rpm)		hp	205			205			245		
Aspiration and Cooling		Turbo Charged and Charge Air Cooled									
Cubic Capacity		Litre	6.8			6.8			6.8		
Cylinders and Build		6 - In Line			6 - In Line			6 - In Line			
Engine Rated Speed		rpm	1500			1500			1500		
Compression Ratio		17.0:1			17.0:1			17.0:1			
Bore and Stroke		mm x mm	106 x 127			106 x 127			106 x 127		
Governor Type		Mechanical			Mechanical			Mechanical			
Fuel Consumption		Load	1/2	3/4	Full	1/2	3/4	Full	1/2	3/4	Full
		L/h.	17.5	25	33.5	17.5	25	33.5	21	31.5	41
Fuel Tank Capacity		Litre	360			360			360		
Total Oil Capacity		Litre	19			19			34		
Coolant capacity (Engine and Radiator)		Litre	34.5			34.5			40		
Air Intake Engine		m ³ / min.	11.2			11.2			11.5		
Exhaust Gas Flow		m ³ / min.	23.1			23.1			32.9		
Exhaust Gas Temperature		0°C	575			575			603		
Alternator Voltage regulation		Plus / Minus %1.5			Plus / Minus %1			Plus / Minus %1			

All Sets Come With Battery Charger and Engine Heater as Standard.

OPEN TYPES

Dimensions (Length x width x height)	m.	2.44 x 1.13 x 1.6		2.35 x 1.13 x 1.6	
Dry Weight	kg.	1495		1535	

SOUND ATTENUATED TYPES

		ASM6			
Dimensions (Length x width x height)	m.	3.27 x 1.16 x 1.9			
Dry Weight	kg.	2010		2050	

Manufacturer reserves the right to make changes in model, technical specifications, colour, equipment and accessories without prior notice.

OPTIONAL EQUIPMENTS**Engine**

Electronic Governor
Remote Radiator

Alternator

3 Pole Output Circuit Breaker
Oversised Alternator
Anti-Condensation Heater

Panel

Transfer Switch
Auto Mains Failure
Earth Fault

**Accessories**

Bulk Fuel Tank
Automatic Fuel Filling Systems
Fuel Water Separator
Low Fuel Alarm
Residential Silencer
Trailer
Tool-Kit for maintenance

Redgen Power Systems, Unit 44 Hemming Road, Redditch, Worcestershire B98 0DH England UK.
tel. +44 (0)1564 78 2066 fax. +44 (0)1564 784785 email sales@redgen.co.uk

