



STANDARD SPECIFICATIONS

The generators in this range are powered by Vanguard engines and are for the most demanding applications and operating conditions. Easy start and maintenance.

Reliability, durability and performance put them at the top of the commercial engine category.. period. In accordance with ISO 8528, ISO 3046.

All generators come with a low oil shut down sensor.

Circuit breaker protected alternator with a choice of panel options makes these generators the perfect choice for professionals.

ISO8528 ratings are given for the altitude below 100 Metres . and 25 Degrees C.

THREE PHASE GENERATING SETS

50Hz Engine, 3000rpm, 4 stroke, OHV									
Model	Max Power 230 / 115 V		Briggs & Stratton Vanguard Type	HP @ 3000 RPM	Oil Safety	Electric Start	Fuel Tank Litres	Run Time @ 50% Load	Weight Kg
	kVA (1) P F 0.8	kW ISO 8528							
ABE 55T	5.5	4.4	185432	9	Yes	No	16	9hr.52Mins	76
ABE 55TE	5.5	4.4	185437	9	Yes	Yes	16	9hr.52Mins	80
ABE 80T	8	6.4	245432	13	Yes	No	16	7hr.16Mins	102
ABE 80TE	8	6.4	245437	13	Yes	Yes	16	7hr.16Mins	106
AB 110TE	11	8.8	350447	18	Yes	Yes	16	4hr.50Mins	117
AB 110TEK	11	8.8	350447	18	Yes	Yes	16	6hr.39Mins	195
Model	Dimensions cm L x W x H		Noise Level 7 metres Lwa dBA		Wheel Kit	Auto Start	Canopy		
ABE 55T	70 x 55 x 63		96	73	Yes	No	No		
ABE 55TE	71 x 55 x 63		96	73	Yes	No	No		
ABE 80T	78 x 56 x 64		97	74	Yes	No	No		
ABE 80TE	78 x 56 x 64		97	74	Yes	No	No		
AB 110TE	91 x 74 x 75		98	75	Yes	Optional	Optional		
AB 110TEK	98 x 62 x 90		92	68	Yes	Optional	Yes		

STANDARD PANEL FEATURES

On-Off button or key switch	
230 V. 15 A schuko socket	
400 V International socket.	
Circuit breaker	
Hours run meter for >6Kw	
Signal Lamp	

Redgen Power Systems, Unit 44 Hemming Road, Redditch, Worcestershire B98 0DH
 England UK.
 tel. +44 (0)1564 782066 fax. +44 (0)1564 784785 email sales@redgen.co.uk

